



## Soft Shackles & Loop Range

Size starts at only 20mm  
 Weight start from a staggering 0.6gms  
 Maximum working load starts from 247Kgs

Available in 5 diameters from 2-5mm  
 Locked even when not under load  
 Available with fixing loop and HLE  
 Simply pull the release line to open the shackle loop  
 No damage to deck, sail or rigging



**Soft shackles** are a perfect evolution from the more traditional stainless steel screw shackles: ten times lighter than stainless steel, locked even when not under load, easy to undo without tools (simply pull the release line to open the shackle loop) and will not damage to deck or rigging.

| Part no. | Description Soft shackle | Rope diameter mm | Shackle length mm | Loop length | Material black | HLE size | Break load Kgs | Max working load | Weight gms |
|----------|--------------------------|------------------|-------------------|-------------|----------------|----------|----------------|------------------|------------|
| R8900    | 2 x 20mm                 | 2                | 20                | n/a         | Dyneema        | n/a      | 990            | 247              | 0.6        |
| R8901    | 2 x 40mm                 | 2                | 40                | n/a         | Dyneema        | n/a      | 990            | 247              | 0.8        |
| R8902    | 2.5 x 20mm               | 2.5              | 2                 | n/a         | Dyneema        | n/a      | 1875           | 468              | 0.9        |
| R8903    | 2.5 x 40mm               | 2.5              | 40                | n/a         | Dyneema        | n/a      | 1875           | 468              | 1.2        |
| R8904    | 2.5 x 60mm               | 2.5              | 60                | n/a         | Dyneema        | n/a      | 1875           | 468              | 1.4        |
| R8905    | 3 x 20mm                 | 3                | 20                | n/a         | Dyneema        | n/a      | 3025           | 756              | 1.4        |
| R8906    | 3 x 40mm                 | 3                | 40                | n/a         | Dyneema        | n/a      | 3025           | 756              | 1.8        |
| R8907    | 3 x 60mm                 | 3                | 60                | n/a         | Dyneema        | n/a      | 3025           | 756              | 2.2        |
| R8908    | 4 x 40mm                 | 4                | 40                | n/a         | Dyneema        | n/a      | 3605           | 901              | 3.4        |
| R8909    | 4 x 60mm                 | 4                | 60                | n/a         | Dyneema        | n/a      | 3605           | 901              | 4.1        |
| R8910    | 4 x 80mm                 | 4                | 80                | n/a         | Dyneema        | n/a      | 3605           | 901              | 4.8        |
| R8911    | 5 x 40mm                 | 5                | 40                | n/a         | Dyneema        | n/a      | 6595           | 1648             | 5.8        |
| R8912    | 5 x 60mm                 | 5                | 60                | n/a         | Dyneema        | n/a      | 6595           | 1648             | 6.7        |

**Soft loops** offer a simple way to attach fittings etc. where space is tight without increasing weight, and removing the risk of damaging to the deck, spars and carbon areas.



| Part no. | Description Loop black | Rope diameter mm | Shackle length mm | Loop length | Material black | HLE size | Break load Kgs | Max working load | Weight gms |
|----------|------------------------|------------------|-------------------|-------------|----------------|----------|----------------|------------------|------------|
| R8930    | 2 x 40mm               | 2                | n/a               | 40          | Dyneema        | n/a      | 700            | 178              | 0.5        |
| R8931    | 2.5 x 50mm             | 2.5              | n/a               | 50          | Dyneema        | n/a      | 900            | 225              | 1          |
| R8932    | 3 x 60mm               | 3                | n/a               | 60          | Dyneema        | n/a      | 1500           | 375              | 1.5        |
| R8933    | 4 x 80mm               | 4                | n/a               | 80          | Dyneema        | n/a      | 3100           | 775              | 3.4        |
| R8934    | 5 x 100mm              | 5                | n/a               | 100         | Dyneema        | n/a      | 4500           | 1125             | 6          |

**Soft shackles with fixing loops** allow the shackle to be undone regularly, without removing the shackle from the boat.



| Part no. | Description Soft shackle with fixing loop | Rope diameter mm | Shackle length mm | Loop length | Material black | HLE size | Break load Kgs | Max working load | Weight gms |
|----------|---|------------------|-------------------|-------------|----------------|----------|----------------|------------------|------------|
| R8950    | 2x40x20mm                                 | 2                | 20                | 40          | Dyneema        | n/a      | 440            | 110              | 1          |
| R8951    | 2x40x60mm                                 | 2                | 60                | 40          | Dyneema        | n/a      | 440            | 110              | 1.3        |
| R8952    | 2.5x50x20mm                               | 2.5              | 20                | 50          | Dyneema        | n/a      | 660            | 165              | 1.6        |
| R8953    | 2.5x50x60mm                               | 2.5              | 60                | 50          | Dyneema        | n/a      | 660            | 165              | 2.3        |
| R8954    | 3x60x20mm                                 | 3                | 20                | 60          | Dyneema        | n/a      | 880            | 220              | 2.9        |
| R8955    | 3x60x60mm                                 | 3                | 60                | 60          | Dyneema        | n/a      | 880            | 220              | 3.6        |
| R8956    | 4x70x20mm                                 | 4                | 20                | 70          | Dyneema        | n/a      | 1100           | 275              | 5.7        |
| R8957    | 4x70x60mm                                 | 4                | 60                | 70          | Dyneema        | n/a      | 1100           | 275              | 7          |
| R8958    | 5x80x40mm                                 | 5                | 40                | 80          | Dyneema        | n/a      | 1320           | 330              | 10.8       |
| R8959    | 5x80x80mm                                 | 5                | 80                | 80          | Dyneema        | n/a      | 1320           | 330              | 12.4       |

**Soft shackles with high load eyes**, produced from HE30 marine grade aluminium, hard coat anodised to 40 microns and PTFE treated, allow higher load application than conventional blocks with very low friction.



| Part no. | Description Soft shackle with HLE | Rope diameter mm | Shackle length mm | Loop length | Material bore black | HLE size | Break load Kgs | Max working load | Weight gms |
|----------|-----------------------------------|------------------|-------------------|-------------|---------------------|----------|----------------|------------------|------------|
| R8970    | 2x20x6mm                          | 2                | 20                | n/a         | Dyneema             | n/a      | 440            | 110              | 1.4        |
| R8971    | 2x80x6mm                          | 2                | 80                | n/a         | Dyneema             | n/a      | 440            | 110              | 2          |
| R8972    | 3x20x10mm                         | 3                | 20                | n/a         | Dyneema             | n/a      | 880            | 220              | 3.4        |
| R8973    | 3x100x10mm                        | 3                | 100               | n/a         | Dyneema             | n/a      | 880            | 220              | 3.9        |
| R8974    | 5x40x12mm                         | 5                | 40                | n/a         | Dyneema             | n/a      | 1320           | 330              | 8.4        |
| R8975    | 5x100x12mm                        | 5                | 100               | n/a         | Dyneema             | n/a      | 1320           | 330              | 8.7        |
| R8976    | 6x100x18mm                        | 6                | 100               | n/a         | Dyneema             | n/a      | 1540           | 385              | 29.3       |